

Support and E-Warranty Certificate https://www.vevor.com/support

WATER STORAGE TANK USER MANUAL

We continue to be committed to offering tools at competitive prices. "Save Half", "Half Price", or any other similar expressions used by us only represent an estimate of savings you might benefit from buying certain tools with us compared to the major top brands and do not necessarily mean to cover all categories of tools offered by us. You are kindly reminded to verify carefully when placing an order with us if you are saving half in comparison with the top major brands.



WATER STORAGE

TANK

MODEL:WT-0240/WT-0330/WT-0540



NEED HELP? CONTACT US!

Have product questions? Need technical support? Please feel free to contact us:

CustomerService@vevor.com

This is the original instruction, please read all manual instructions carefully before operating. VEVOR reserves a clear interpretation of our user manual. The appearance of the product shall be subject to the product you received. Please forgive us that we won't inform you again if there are any technology or software updates on our product.

NOTES

- 1. Keeping the outlet valve closed, fill in the liquid from the inlet valve on the top.
- 2. The diameter of the water injection tube should be less than 1.5" so that the air in the tank can be discharged.
- 3. Ensure all accessories are firmly tightened by hand. Improper tightening of accessories can lead to leakage.

MODEL AND PARAMETERS

| Model | WT-0240 | WT-0330 | WT-0540 | | | |
|--------------|-------------|-------------|-------------|--|--|--|
| Capacity | 240L | 330L | 540L | | | |
| Material | PVC | PVC | PVC | | | |
| Ambient | -30℃~+70℃ | -30℃~+70℃ | -30℃~+70℃ | | | |
| temperature | | | | | | |
| Color | Black | Black | Black | | | |
| Product Size | 100x70x35cm | 120x80x35cm | 150x90x40cm | | | |

TRUCTURE DIAGRAM



1.Top intake(1.5")3.Bag body

2. Hanging ring(It's actually at four corners)

4.Scale

5.Drain valve(1.5")

COMPONENTS

| No. | PART | NAME | QTY |
|-----|---|-------------|-----|
| 1 | | Rain bag | 1 |
| 2 | | Drain valve | 1 |
| 3 | | Patch | 2 |
| 4 | VEVOR Was a service of the service | User manual | 1 |

USE AND CLEAN

1. After getting the product, unroll the rain bag. The water inlet is at the top.



2. Install water outlet valve(Clockwise tightening). The outlet valve is larger and needs to be installed more forcefully until the valve is centered.



MAINTAIN AND STORAGE

- 1. Please use mild detergent and water for cleaning.
- 2. Don't scrub with hard objects like brushes.
- 3. Dry before storage.Do not store in a dark, damp place.
- 4. Clean the debris at the filter port in time to avoid clogging.
- 5. If the barrel body is damaged, it can be repaired with the attached patch (Please bring your own glue).
- 6. If the joint is leaking, tighten the joint or wrap waterproof tape(Provide for yourself) on the thread of the joint before installing it(As shown below).



Note: If you install and remove the connector yourself and the switch is not vertical, try increasing the number of winding laps of waterproof tape.

Manufacturer: Haining Tak Techtextil Industries Co., Ltd.

ADD: No. 2, Qingyuan Road, Xieqiao Town, Haining City, Jiaxing City, Zhejiang

Province, China

Importer: WAITCHX

Address: 250 bis boulevard Saint-Germain 75007 Paris

Importer: FREE MOOD LTD

Address: 2 Holywell Lane, London, England, EC2A 3ET

EC REP

EUREP GmbH Unterlettenweg 1a, 85051 Ingolstadt, Germany

UK REP

EUREP UK LTD UNIT 2264, 100 OCK STREET, ABINGDON OXFORDSHIRE ENGLAND OX14 5DH

Made in China



TOUGH TOOLS, HALF PRICESupport and E-Warranty Certificate
https://www.vevor.com/support